



RXSOL

CHEMO PHARMA INTERNATIONAL

Technical Data Sheet (TDS)

RXSOL-16-1042-025

Rig Wash Liquid

RIG WASH LIQUID

RXSOL-16-1042-025

Product Introduction:

CONCENTRATE CLEANER & DEGREASER ::---

Powerful and concentrated oil cleaning formulation for Quick removal of oil, grease, grimes from oilfield and industrial surface area. Due to its high emulsification property it cleans and dissolves grease, oily dirt, and thick grime build up from heavy equipment, machinery, tools, concrete floors and metal surfaces.

Best results also achieved as a tank cleaner and gas freeing for double bottom tanks, wing tanks, pipe lines, fuel oil tanks, etc

Due to free from caustic and Hydrocarbon very gentle on hands & ideal for cleaning Walls Wood works, Metals and all areas . Acts as superior quality cleaner / degreaser . BIO DEGRADABLE

FIELDS :

RXSOL-16-1042-025 containing corrosion inhibitors to prevents the corrosion of metals such as Aluminium, Copper, Brass and Tin. **RXSOL-16-1042-025** is designed to clean Animal / Vegetables oils, Fats, Hydrocarbon removes Dirt, link, Carbonized grease, Oil, Heavy oils etc. **Specialized for all types of cleaning and degreasing**. may be applied by brush, handspray or used in ultrasonic cleaning tanks, immersion soak tanks and high and low pressure spray appliances. May be used neat or diluted by up to 50 parts of water according to the amount and type of soil to be removed. **Tank Cleaning** (Cargo tank cleaning after mineral, animal, vegetable and fish oil.)

Method of Application and Doses :

1st of all by stripping suction removes all possible oil (greasy materials). To prevents evaporation of lighter fraction oil flush the system with cold water. **May be brushed on, sprayed (Hand spray/Direct injection) recirculate the system with RXSOL-16-1042-025 Solution.**

1	Cleaning with washing machines. Dose rate: 0.3-5 ltr per ton wash water (0.03-0.5%).
2	Cleaning with recirculation method. Dose rate: 0.5-10 ltr per ton wash water (0.05-1%).
3	Spot cleaning. Hand sprayed neat or diluted up to 1-10 parts water and left for about 15-20 minutes before .washing.off

DOSAGE :

Nature Of Residue Veg Oil (Drying/Non Drying Fish Oil,Alcohol,Acids,Amines)	HAND SPRAY 1-10%	DIRECT INJECTION 0.03-0.5%	CIRCULATION 0.05-0.7 %
Organic Material (Hydrocarbon)	NA	0.0 5-0.5%	0.05-0.7%

Product Properties	CHARACTERISTICS	
Appearance	Pale yellow clear liquid	Compatible with oily water separators.
Oodour / Solubility	NONE / INFINITE IN WATER.	Releasing the oil phase for reclamation. Suitable for all types of floors.Deodorizing nature
Density	In g/cm3 at 15°C: 1.0 +/- 0.05	Eliminates the need to buy & stock duplicate products because of its effectiveness.
Compatibility		An economic highly concentrated product.
Metal Rubber	May attack Zinc at concentrated solutions No known effect	Also used for gas and hydrocarbon freeing of tanks. Free from caustic & hydrcarbon, Non flammable Water based , Biodegradable .Safe to metal
pH Neat	7.5 to 8.5	PACKAGING : RXSOL-16-1042-025 -25 kg ,50 kg.

RXSOL-16-1042-025 has numerous general cleaning applications including the removal of greases, oil, sludge, carbon deposits, general dirt and grime. Can be used as engine room cleaner. Suitable for cargo tank cleaning. Can be used as accommodation cleaner for bulkheads, decks, toilets. Suitable for cleaning of soiled textiles as rugs, covers, mats, overalls, etc. Effectively cleans glass fibre boats, hulls and painted surfaces

Read the Material Safety Data Sheet before using this products:

This Safety Data Sheet is provided by RXSOL. For the most current version of this document, please visit eastindiachemicals.com. This document is prepared in accordance with GHS / OSHA HazCom standards. The information contained herein is believed to be accurate but does not purport to be all-inclusive. It is the responsibility of the user to determine the suitability of this information for their application.