



RXSOL

CHEMO PHARMA INTERNATIONAL

Technical Data Sheet (TDS)

RXSOL-17-3105-025
FLOCCULANT

General Description

RXSOL Flocculant is a very effective liquid treatment based on Poly chloride to separate oil residues from bilge water. It is iron-free, and is completely safe to the environment.

Features

- Cost-effective bilge water treatment based on specially selected Poly Aluminium Chloride
- Iron-free. Completely safe to the environment
- Acts by both breaking the oil-in-water emulsion and by building flocs
- Helps to meet environmental regulations on oil content. Discharged water contains normally less than 3 ppm oil
- Remaining oil sludge can be burned onboard or pumped ashore-contains very little water
- Low dosage, economical use
- Effective over an extended pH-range. Eliminates the use of pH-stabilising chemicals
- Approved by manufacturers of bilge water cleaning systems

Applications

International environmental regulations set strict rules as to the oil content in effluent water from ships. To meet these regulations, a combination of mechanical and chemical cleaning is necessary. Bilge Water Flocculant is used in combination with multistage bilge water cleaning systems that include mechanical separation of free oil, emulsion breaking, flocculation and filtration. After dosing, Bilge Water Flocculant breaks the oil-in-water emulsion created by contaminants in lubricating and fuel oils, emulsifying cleaning agents etc. It then destabilizes the remaining small oil droplets and agglomerates them into larger particles (flocs) that are easily collected by filtering.

Directions for use

Dosing method

Typical dose rate: 100 - 500ppm (0.1 - 0.5 litre/m³ of water) In a multistage bilge water cleaning system, Bilge Water Flocculant is fed undiluted through a dosage pump connected to the pressure side of the oil descaler. The flocc tank is fed according to the flow of the bilge water pumped into it. The feed is adjusted in connection with the installation and normally needs no alteration. If required, dosing can also be controlled by measuring the level in the container.

Further Technical Data

Form	Liquid
Appearance	Clear
Density	1,3

pH, in conc. 1,3

Not Compatible Corrosive to cast iron as concentrate. Non-corrosive to all metals at use concentration.

This Safety Data Sheet is provided by RXSOL. For the most current version of this document, please visit eastindiachemicals.com. This document is prepared in accordance with GHS / OSHA HazCom standards. The information contained herein is believed to be accurate but does not purport to be all-inclusive. It is the responsibility of the user to determine the suitability of this information for their application.