



RXSOL

CHEMO PHARMA INTERNATIONAL

Technical Data Sheet (TDS)

RXSOL-19-1016-025

Sewage Defoamer

Description :::

This is a non- silicone based water dispersible, liquid emulsion. It controls foaming in sewage and waste water systems and collecting tanks in vacuum toilet systems.

Dose :::

Typical dosage is 10 to 30 ml / ton, but proper dosage rate to be found out on site testing . The recommended dosing method for sewage system is to premix 1 part of **RXSOL-19-1016** with 5 parts of fresh water and pump this into the EVAC ejector tank . The dosing is done about 1/2 hour before top load.

This Safety Data Sheet is provided by RXSOL. For the most current version of this document, please visit eastindiachemicals.com. This document is prepared in accordance with GHS / OSHA HazCom standards. The information contained herein is believed to be accurate but does not purport to be all-inclusive. It is the responsibility of the user to determine the suitability of this information for their application.