



RXSOL

CHEMO PHARMA INTERNATIONAL

Technical Data Sheet (TDS)

RXSOL-42-1524-050

CHEMZOL 9200

RXSOL-42-1524-050 is a easy to handle liquid solution that can be used as both a powerful oxygen scavenger for low and medium pressure steam boilers and also a neutraliser for removing chlorine and other biocides to protect sensitive systems such as RO plants or prior to discharge to the environment. RXSOL-42-1524-050 is intended for applications such as the food industry where formulations including heavy metal catalysts cannot be used.

Application and Dosage

As Boiler Water Oxygen Scavenger

Rapid reaction with oxygen ensures efficient protection of feedlines and boilers from corrosion. RXSOL-42-1524-050 is intended for those applications such as the food industry where heavy metal catalysts cannot be used. RXSOL-42-1524-050 reacts with oxygen to form bi-products which have no adverse effect on boiler integrity. One of these bi-products enhances protection against caustic embrittlement. RXSOL-42-1524-050 should be dosed at the rate of 18ml/m³ for every ppm of dissolved oxygen. A reserve of approximately 50ppm of sulphite should be maintained in the boiler water.

As Biocide Neutralizer

RXSOL-42-1524-050 is an effective neutraliser of halogens, particularly chlorine, and a wide range of other biocides. It can be used to neutralise excess chlorine following disinfection of water systems, including cooling water systems and the feed to RO systems. RXSOL-42-1524-050 can also be used to prepare waste streams for disposal to treatment services, including public utility services, by conditioning residual biocide including, but not limited to, C/MIT, DBNPA and THPS.

RXSOL-42-1524-050 is dosed at the rate of 7 - 10 ml/m³ per mg/l of free chlorine

Specification

Parameter	Result
Appearance	Clear Solution
Odour	Characteristic
pH	5-6
Density	>1.2

Features and Benefits

- Reacts with oxygen to produce compounds that do not harm boiler integrity. One of these compounds further improves protection against caustic embrittlement.
- Suitable for low and medium pressure boilers
- Catalysed product to ensure efficient protection from corrosion

This Safety Data Sheet is provided by RXSOL. For the most current version of this document, please visit eastindiachemicals.com. This document is prepared in accordance with GHS / OSHA HazCom standards. The information contained herein is believed to be accurate but does not purport to be all-inclusive. It is the responsibility of the user to determine the suitability of this information for their application.